MG-R(SVR)
Technical Guidance

- General Description of How MG-R(SVR) Technology Works -

April 6, 2004

Toshiya Kaihoko
Senior Engineer
Personal Audio Company, IT & Mobile Network Company

Sony Corporation

MG-R(SVR)
Technical Guidance

1. Requirements for Media and Devices
2. Content Recorded With MG-R(SVR)
3. Retrieving Common Key with EKB and DNK
4. Revocation Using Renewed EKB
5. Procedure of Recording Content
6. Procedure of Playing Back Content
7. Propagation of New EKB Files to Revoke DNKs
8. Secure Authenticated Channel
9. Method of Binding Content to the Medium
10. Prevention of Re-transmission to the Internet
11. Renewal of Software Secure Video Module
12. Hi-MD 1GB and Hi-MD 300MB Media

Requirements for Media and Devices

MG-R(SVR) Device

Secure Video Module (MG-IP)

- Encrypts Content
- Decrypts Content
- Key Management

DKS (Device Key Set)

Unique **ID**
Unique **DNK** (Device Node Key)
Default **EKB** (Enabling Key Block)

MG-R(SVR) Media

Memory Stick PRO

Hi-MD

Media Unique ID
Hidden Area
General Purpose Area

F:\
file edit ...

word

cture

F:\
file edit ...

text   file   word

data   movie   picture

For details, see Section 3,4 and 5, Figure 1 and 2 in the Technical Guidance Document

Content Recorded With MG-R(SVR)

Content

Common Key (Kmgr)

CCI, EPN..

Content Key (Kc)

Content

= BF Content

Encrypted with Kc, AES 128bit

Content Control Related Information

= "EPN" and "Copy Control not Asserted" for BF Content

EKB File

Playback Device Control Information

DKS

Unique ID

DNK

Default EKB

Secure Video Module (MagicGate)

Common Key (Kmgr)

EKB: Enabling Key Block
DKS: Device Key Set
DNK: Device Node Key

For details, see Section 8 and Figure 6 in the Technical Guidance Document

Retrieving Common Key with EKB and DNK

DNK

EKB → **Process_EKB**

EKB on a medium or
on a device is used.

**Common Key
(Kmgr)**

EKB: Enabling Key Block
DNK: Device Node Key

For details, see Section 9 and Figure 7 in the Technical Guidance Document
See also Section 5 and Figure 5.1 in the MG-R(SVR) Specification - Informational Version

Revocation using Renewed EKB

EKB

Common Key

Common Key is renewed

New EKB

New Common Key

Playback Device Control Information

Playback Device Control Information is renewed

New Playback Device Control Information

New Playback Device Control Information has information to revoke device #A

DNK

EKB → **Process_EKB**

Common Key (Kmgr)

New EKB → **Process_EKB**

which has the New Playback Device Control Information to revoke device #A

Compromised **DNK** at Device #A

cannot retrieve New Common Key

"Revoke"

EKB: Enabling Key Block
DNK: Device Node Key

For details, see Section 10 and Figure 8 in the Technical Guidance Document
See also Section 5 and Figure 5.2 in the MG-R(SVR) Specification - Informational Version

Procedure of Recording Content

Device

Medium

EKB file

Content

DKS

Default
EKB

DNK

③

Encrypted Kc
(by Kmgr)

Encrypted
Content
(by Kc)

②

④

⑤

Decrypt

Encrypt

Encrypt

①

**Common Key
(Kmgr)**

**Content Key
(Kc)**

**Content**

EKB: Enabling Key Block
DKS: Device Key Set
DNK: Device Node Key

Procedure of Playing Back Content

Non-Revoked Device

Medium

Revoked Device

EKB file

Content

DKS

Default EKB

DNK

EKB file

DKS

Default EKB

DNK

Decrypt

Decrypt

Decrypt

Decrypt

Kmgr

Kc

Content

Revoke

With a Revoked DNK, Secure Video Module cannot retrieve the Common Key(Kmgr) and therefore cannot obtain the Content Key. This means it is Revoked.

For details, see Section 11.2 and Figure 10 in the Technical Guidance Document

Propagation of New EKB Files to Revoke DNKs

EKB(#n)

EKB(#n+1)

EKB(#n+1)

MG-R(SVR) Server

EKB (#n+1)

EKB (#n+1)

EKB (#n)

EKB (#n+1)

EKB (#n+1)

EKB (#n+1)

EKB (#n+1)

EKB (#n) : Older EKB

EKB (#n+1) : New EKB

Revoke

Device That Has a Revoked DNK

EKB: Enabling Key Block
DNK: Device Node Key

Secure Authenticated Channel

Secure Video Software on PC

(example configuration)

Device

MG-R(SVR) Application Software   file edit ...

USB

Application Software

MG | DKS

Device Key Set

USB I/F

MG

Secure Video Module (MagicGate)

USB protected using SAC

MG-R(SVR) Application Software   file edit ...

Application Software

MG | DKS

OS

USB I/F

CPU | DSP

MG | Hi-MD Drive I/F

MG-R(SVR) Application Software   file edit ...

For details, see Section 7 and Figure 5 in the Technical Guidance Document

Method of Binding Content to the Medium

F:\Video

Content_1   Content_2   Content_n   Content_M

General Purpose Area

$C\_MAC(n) = Hash(\ Content\ Key,$
$Content\ Protection\ Related\ Information\ )$

MACLIST to Check each contents integrity

Latest EKB

All C_MAC value are gathered in MACLIST file.

Hidden area

ICV in Hidden Area

MG-R(SVR) Compliant Devices can access the Hidden Area

ICV
(Integrity Check Value)

$ICV = Hash(\ Media\ ID,\ Latest\ EKB,\ C\_MAC(1),....,C\_MAC(\#M))$

Unique Media ID

non changeable ID

MAC: Message Authentication Code
C_MAC: Content MAC
ICV: Integrity Check Value
EKB: Enabling Key Block

Prevention of Re-transmission to the Internet

the Internet

F:\	

Video EKB file MAC list

ICV

Hidden area

Media ID #N

✕ **COPY**

|	
F:\	

Video EKB file MAC list

Hidden area

Media ID #M

Different Media ID and No ICV,
Therefore Integrity Check Fails
and Playback is Blocked

ICV: Integrity Check Value
EKB: Enabling Key Block

For details, see Section 14 and Figure 13 in the Technical Guidance Document

Renewal of Software Secure Video Module

(software implementation only)

Revoked Software

Renewal Completed

New EKB & Secure Module

Secure Software module #n

Secure Software module #n+1

Renewal of Software Secure Video Module

EKB(n+1)

Secure Software module #n+1

Replacement

Update Server & CD-ROM

Update Server

CD-ROM

For details, see Section 15 Figure 13 in the Technical Guidance Document

Hi-MD 1GB and Hi-MD 300MB media

Hi-MD media are categorized in two types, and their Media Unique IDs are written as follows:

Hi-MD 1GB

Media Unique ID is written onto a Hi-MD 1GB medium when it is produced by a licensee of MG-R(SVR) for Hi-MD media

MiniDisc (for Audio)

Hi-MD 300MB

Compliant Device writes the Media Unique ID onto a Hi-MD 300MB when formatting it. Media Unique ID is never changed (except when media are formatted, which erases all content)

All Hi-MD Compliant Devices can format MiniDisc media as Hi-MD 300MB media

---

For details, see Section 3 in the MG-R(SVR) for Hi-MD - Technical Guidance Document

Summary

- Each MS PRO or Hi-MD medium has a Media Unique ID and a Hidden Area
- Hidden Area can be accessed only by MG-R(SVR) Compliant Devices
- Device has a Secure Video Module and a Device Key Set
- Content is encrypted by the Content Key (Kc);

  Content Key is encrypted by the Common Key (Kmgr);

  Common Key is retrieved from EKB (Enabling Key Block) and DNK (Device Node Key)
- SAC (Secure Authenticated Channel) protects secure information transferred on USB
- Content is protected from alteration using Integrity Check Value (ICV): a hash of content data, content protection related information, and Media Unique ID
- ICV stored in Hidden Area also prevents illegal retransmission of the content
- Content cannot be copied bit-by-bit (such copies will not play)
- Media Unique ID on Hi-MD 300MB is written by Hi-MD Devices, but is never changed except when being formatted